



SGP - TR - 30

CONF-781222-26

**PROCEEDINGS
FOURTH WORKSHOP
GEOTHERMAL RESERVOIR ENGINEERING**

**Paul Kruger and Henry J. Ramey, Jr.
Editors**

December 13-15, 1978



**Stanford Geothermal Program
INTERDISCIPLINARY RESEARCH
IN ENGINEERING AND EARTH SCIENCES
Stanford University, Stanford, California**

AN EVALUATION OF JAMES' EMPIRICAL FORMULAE FOR THE DETERMINATION
OF TWO-PHASE FLOW CHARACTERISTICS IN GEOTHERMAL WELLS

P. Cheng and M. Karmarkar
University of Hawaii
Honolulu, Hawaii 96822

Introduction

One of the most economical and simple methods of determination of two-phase flow parameters in geothermal well testing is the so-called James' method [1,2]. The method consists of the measurements of lip pressure (p), and the flow rate of water (w) by a conventional weir. The stagnation enthalpy (h_0) is then determined from a plot showing h_0 versus $w/p^{0.96}$ which is empirically determined by James [1,2]. The mass flow rate is then determined from the following empirical formula

$$G = 11,400 \frac{p^{0.96}}{h_0^{1.102}} \quad (1)$$

where G is the total mass flow rate in $\text{lb}_m/\text{sec-ft}^2$, p is the lip pressure in psia, and h_0 is the specific enthalpy in BTU/lb_m . The above relation is empirically determined for discharge pressure up to 64 psia and pipe diameters up to 8". For pipe diameters smaller than 0.2", it has been suggested that the value of 11,400 be replaced by 12,800. In view of the widespread use of the James' method, it is important to assess its accuracy and range of applicability.

Two-Phase Critical Flow Theory

In this paper we shall compare the wellbore discharge characteristics obtained from James' empirical formulae to those predicted by Fauske's two-phase critical flow theory [3]. Fauske suggested that in two-phase flow the maximum discharge rate may not necessarily be accomplished by a shock front. He proposed that at the critical flow condition the absolute value of the pressure gradient at a given location is maximum but finite for a given flow rate or quality, i.e.,

$$(dp/dz)_{G,x} = \text{maximum and finite}, \quad (2)$$

where z is the coordinate along the streamwise direction, and x the quality of the saturated mixture.

Under the assumptions of (i) annular flow pattern, (ii) two-phases

in thermal equilibrium, (iii) negligible frictional loss, and (iv) one-dimensional steady flow, Fauske [3] obtained the following analytical expression for the critical flow rate of a saturated mixture:

$$G_{\text{critical}} = \left[g_c k / Q \right]^{1/2} \quad (3)$$

where $Q = - [(1-x+kx) x (dv_g/dp) + (v_g(1+2kx-2x) + v_f(2xk-2k-2xk^2+k^2)) dx/dp]$,

$$g_c = 32.2 \frac{\text{lb-ft}}{\text{lb}_f\text{-sec}^2} , \text{ and } k = (v_g/v_f)^{1/2} \text{ with } v_g \text{ and } v_f \text{ denoting}$$

the specific volume of the saturated vapor and liquid respectively. Thus, the critical flow rate can be calculated from Eq.(3) if the steam quality and the lip pressure are known.

The corresponding stagnation enthalpy can be determined from

$$h_0 = h_f(1-x) + h_g x + (G^2/2g_c) \left((x^3 v_g^2 / Rg^2) + (1-x)^3 v_f^2 / (1-Rg)^2 \right) / J , \quad (4)$$

where R_g is the gas void fraction which is related to steam quality [4]. In comparison with experimental data, Levy [4] found, however, that using Eq.(4) for the computation of h_0 would lead to under-prediction of the mass flow rate. For this reason we shall compute the stagnation enthalpy on the basis of a homogeneous model, i.e.,

$$h_0 = h_f(1-x) + h_g x + G^2 v_h^2 / 2g_c J , \quad (5)$$

where $v_h = v_f(1-x) + v_g x$ and $J = 778 \text{ ft-lb}_m/\text{BTU}$.

The weir flow rate is then determined from

$$w = G(1 - x) . \quad (6)$$

Results and Discussion

For a given set of values of lip pressure and steam quality and with the data of saturated steam-water properties [5], Eq.(3) can be used for the computation of total mass flow rate G . The stagnation

enthalpy and the weir flow rate are then determined from Eqs.(5) and (6). The results of the computations for the lip pressure from 14.7 psia to 200 psia for geothermal well testing applications are plotted in Figs. 1 and 2. When the lip pressure and the weir flow rate are measured in a geothermal well test, the stagnation enthalpy of the reservoir, the steam quality at the well head, and the total mass flow rate can easily be determined from these plots.

To assess the accuracy of the James' method, calculations were carried out for five different sets of lip pressure and weir flow rate using James' empirical formulae and Fauske's theoretical prediction (i.e., Figs. 1 and 2). The results for total mass flow rate, the stagnation enthalpy, and the steam quality are tabulated in Table 1 for comparison. It is shown that the results based on the two methods differ within 8%.

References

1. James, R., "Measurement of Steam Water Mixtures Discharging at the Speed of Sound to the Atmosphere, New Zealand Engineering, pp. 437-441 (1966).
2. James, R., "Steam-Water Critical Flow Through Pipes," Proc. Inst. Mech. Engrs., v. 176, pp. 741-748 (1962).
3. Fauske, H., "Contribution to the Theory of Two-Phase, One Component Critical Flow," Argonne National Laboratory, Rept. No. ANL-6633 (1962).
4. Levy, S., "Prediction of Two-Phase Critical Flow Rate," A.S.M.E. Paper 64-HT-8.
5. Keenan, J. and Kays, Keys, F. G., Steam Tables, John Wiley and Sons, Inc., New York, N.Y. (1969).




Fig. 1. Weir Flow Rate vs. Stagnation Enthalpy at Selected Values of Lip Pressure According to Fauske's Theory




Fig. 2. Weir Flow Rate vs. Steam Quality at Selected Values of Lip Pressure According to Fauske's Theory.

Table 1. COMPARISON OF RESULTS BASED ON THE JAMES' METHOD
AND FAUSKE'S ANALYTICAL MODEL

Case	p (psia)	w (lb _m /sec-ft ²)	h _o BTU/lb _m	G lb _m /sec-ft ²	x	Method
1	14.7	40	736.90	88.44	.54	Fauske (F)
			800.00	95.13	.58	James (J)
2	25.0	85.5	698.78	164.59	.48	F
			750.00	170.06	.50	J
3	60.0	226.0	697.79	403.39	.44	F
			715.00	415.42	.46	J
4	100.0	105.0	1004.52	419.84	.75	F
			985.00	476.60	.78	J
5	150.0	53.0	1148.87	523.41	.90	F
			1130.00	590.00	.90	J